sealersplu

STRIP-IT

Heavy Duty Sealer, Coating, Graffiti and Epoxy Grout Haze Remover

DESCRIPTION: STRIP-IT is a Professional Grade, safer, nonflammable, heavy duty multi-purpose sealer and coating remover. Formulated to stay wet for longer periods to give the product time to break down and help remove most sealers, coatings, epoxy grout haze, urethanes, synthetic finishes, adhesives, silicone, paint, ink, marker, deep-set oil stains and heavy wax and grease build up. For indoor, outdoor, domestic, commercial and industrial areas

USE: For Porcelain, Ceramic, Encaustic and Tessellated Tiles, Terrazzo, Grout, Bricks, Pavers, Concrete, Mosaics, Terracotta, Saltillo, Quarry Tiles, Engineered Stone, All Natural Stone e.g. Basalt, Bluestone, Granite, Marble, Limestone, Quartz, Sandstone, Slate, Travertine etc.

TEST FIRST: Always test first in an inconspicuous area to determine ease of application, dwell time, colour stability and desired results. User must determine suitability for their use.

PRECAUTIONS & SAFETY DIRECTIONS:

- 1. Read entire label, SDS & technical bulletin before using;
- 2. Wear appropriate gloves, skin and eye protection;
- 3. Do NOT breathe in fumes or vapours wear appropriate mask. Use in a well ventilated area;
- 4. Avoid contact during pregnancy or while nursing;
- 5. Use when surface temperature is between 4°C & 32°C;
- 6. Do NOT allow contact with painted or waxed surfaces;
- 7. Do NOT mix with other chemicals;
- 8. Floor will get slippery during process. Take appropriate precautions to prevent slips and falls;
- 9. Will affect sealers, coatings, floor finishes, deck stains & painted surfaces:

HOW TO USE QUICK GUIDE:



Pour product into a suitable container



Spread product evenly to the surface



After the appropriate dwell time, scrub



For large areas, use a slow speed scrubber



nove dirty solution with a wet vac



IMPORTANT NOTES:

- 1. Surface ready for light traffic after 1 hour or after all fumes and vapours have dissipated;
- 2. Allow at least 48 hours drying time before applying any sealers, coatings or floor finishes. Always do a test area before applying new sealer or coating to the whole area to test any adverse reaction.

LIMITATIONS:

- Removal of thick or multiple coatings may require multiple applications of STRIP-IT;
- Refer to SEALERSPLUS.COM.AU for appropriate stain removal or problem solving product.

COVERAGE: Approximately 10-40m² per litre. Coverage will vary depending on type and severity of the problem you are trying to remove, porosity of surface, time solution is left to dwell on the surface and weather conditions.

HANDLING, STORAGE & CLEAN UP:

- Close container tightly after each use and keep upright;
- Store locked up in original container in a well ventilated cool area & protect from sunlight:
- Shelf life is approx 3 years in unopened container less after
- Storage beyond that time does not necessarily mean the product is not usable.
- Do a test area first. Do not re-use container. Rinse and discard in
- Wash tools, gloves and shoes with water before they dry;
- WASH UNDERSIDE OF SHOES BEFORE STEPPING ONTO OTHER

FIRST AID: Immediately Contact Poisons Centre (Australia Ph. 131-126, NZ Ph: 0800 764-766) or a doctor. INGESTION: Rinse mouth. Do NOT induce vomiting. EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing. CLOTHES: Remove contaminated clothing and wash before use; SKIN & HAIR: Wash with plenty of soap and water. INHALATION: Remove victim to fresh air and keep at rest in a comfortable position for breathing; GENERAL: If any irritation persists get medical advice.

HOW TO USE:

- 1. Do NOT dilute. Use neat.
- 2. Using a roller, mop, brush or sponge, carefully apply a liberal amount of Strip-It to a manageable area;
- 3. Allow minimum dwell time of 30 minutes up to 2 hours depending on the problem (the longer the better);
- 4. DO NOT ALLOW PRODUCT TO DRY ON SURFACE ADD MORE STRIP-IT TO KEEP IT WET AND ACTIVE;
- 5. Scrub with a white nylon pad, scrub brush or scrub machine;
- 6. Remove the dirty solution with a wet vac or mop;
- 7. Rinse thoroughly with clean water;
- 8. Repeat the process as necessary.

NOTE: To help with residue removal, apply XTREMECLEAN+ diluted 1:5 with water to the surface after STEP 7, then scrub again,

PRODUCT WARRANTY - SEALERS PLUS (An Aqua-Seal brand) "The Manufacturer" warrants to the original purchaser of its products that such products are free from manufacturing defect and does not warrant or guarantee the workmanship performed by any person or firm installing its products. The manufacturer's obligation under this warranty is limited solely to the original purchaser and solely shall be limited to the replacement of the product sold or refund. This warranty will not extend to any product which has been modified in any way or which has not been used in accordance with the printed instructions. The manufacturer makes no other warranties either expressed or implied. The end user must determine the suitability of the product for their intended use ALWAYS READ ENTIRE LABEL, SDS & TECHNICAL BULLETIN BEFORE USE & TEST FIRST.



